Performance Evaluation of Smoothing Algorithms for Transmitting Prerecorded Variable-Bit-Rate Video*

Wu-chi Feng
Computer and Information Sciences
Ohio State University
Columbus, OH 43210
wuchi@cis.ohio-state.edu

Jennifer Rexford
Networking and Distributed Systems
AT&T Labs – Research
Florham Park, NJ 07932
jrex@research.att.com

Abstract

The transfer of prerecorded, compressed variable-bit-rate video requires multimedia services to support large fluctuations in bandwidth requirements on multiple time scales. Bandwidth smoothing techniques can reduce the burstiness of a variable-bit-rate stream by transmitting data at a series of fixed rates, simplifying the allocation of resources in video servers and the communication network. Given a fixed client-side playback buffer, several bandwidth smoothing algorithms have been introduced that are provably optimal under certain constraints. This paper compares the transmission schedules generated by the various smoothing algorithms, based on a collection of metrics that relate directly to the server, network, and client resources necessary for the transmission, transport, and playback of prerecorded video. Due to the scarcity of available trace data, we have constructed a video capture testbed and generated a collection of twenty full-length, motion-JPEG encoded video clips. For the sake of comparison, the experiments also evaluate a collection of MPEG-1 clips. Using these video traces and a range of client buffer sizes, we investigate the interplay between the performance metrics and the smoothing algorithms. The results highlight the unique strengths and weaknesses of each bandwidth smoothing algorithm, as well as the characteristics of a diverse set of motion-JPEG and MPEG video clips.

Keywords: video-on-demand server, compressed video, bandwidth smoothing, video traces, traffic management

EDICS: 5-BEEP (Multimedia Traffic Management)

1 Introduction

Many emerging multimedia applications, such as distance learning and entertainment services, rely on the efficient transfer of prerecorded video. Video-on-demand servers typically store video on large, fast disks [1, 2, 3, 4], as shown in Figure 1; the server may also include tertiary storage, such as tapes or optical jukeboxes, for holding less frequently requested data [5]. A network connects the video servers to the client sites through one or more communication links. The network can help ensure the

*An earlier version of this paper appeared in *Proc. IEEE INFOCOM, April 1997.* Since then we have added several other smoothing algorithms and have included the results from MPEG encoded video streams.



Figure 1: **Video-On-Demand Architecture:** This figure shows a basic video-on-demand architecture consisting of video servers, a communication network, and client sites. Possible clients include workstations and set-top boxes that contain hardware to interact with the network and a disk (or RAM) that serves as a playback buffer.

continuous delivery of the video data by including support for rate or delay guarantees [6, 7], based on resource reservation requests from the video server. Client sites include workstations and set-top boxes that have a playback buffer for storing one or more video frames. In this paper, we evaluate techniques that capitalize on this buffer space to reduce the server and network resource requirements for streaming stored video.

High-quality video requires a large amount of storage space and network bandwidth. Even effective compression techniques, such as MPEG [8] and motion-JPEG [9], still result in video streams with bandwidth requirements in the range of 2-10 megabits/second. Many video encoders generate constant-bit-rate (CBR) streams to simplify the allocation of disk, memory, and network resources. However, CBR-encoded video ultimately has variable quality, since the encoder is not permitted to increase the output bit rate during periods of action or detail, precisely when degradation in quality would be most noticeable to the viewer. Alternatively, video encoders can generate constant-quality video, resulting in a variable-bit-rate (VBR) stream. Constant-quality video typically has higher quality than a constant-bit-rate stream with the same average bandwidth [10, 11]. However, constant-quality video can exhibit significant burstiness on multiple time scales, due to the natural variations within and between scenes, as well as the frame structure of the encoding algorithm [12, 13, 14, 15, 16].

The efficient transfer of constant-quality video requires effective techniques for handling burstiness. Although the server, network, and client could conceivably allocate resources based on the peak bit rate of the stream, such over-provisioning is extremely wasteful and undermines the benefits of a constant-quality encoding. Alternatively, resources could be allocated based on certain assumptions about how a variable-bit-rate stream would multiplex with other traffic. Models based on statistical multiplexing, and particularly the theory of effective bandwidth, are useful for network provisioning,

particularly on high-bandwidth links that carry a large number of traffic streams. However, statistical multiplexing does not offer deterministic guarantees and is less useful on lower-bandwidth links that multiplex a small or moderate number of streams. Despite rapid increases in backbone capacity in recent years, most broadband access networks cannot carry more than a handful of high-quality video streams at a time. Instead of relying on statistical multiplexing to handle burstiness, we believe that it is necessary to reduce the variability of individual video streams.

Prerecorded video offers a unique opportunity to reduce the variability of the network bandwidth requirements by transmitting large frames to the client playback buffer in advance of each burst. Capitalizing on *a priori* knowledge of the frame sizes, the server can precompute a transmission schedule that minimizes the bit rate while avoiding both underflow and overflow of the client buffer. This basic observation has been the underpinning of a class of *bandwidth smoothing* algorithms for stored video [17, 18, 19, 20, 21, 22, 23, 24]. Each of these algorithms can compute a transmission schedule for an N-frame video steam, given frame sizes f_i, $i = 1, 2, \ldots, N$, and a b-bit client buffer. Bandwidth smoothing offers substantial reductions in the peak and variability of bandwidth requirements for transmitting constant-quality video. These benefits come from removing short-term burstiness (e.g., at the MPEG group-of-pictures level), as well as the medium-term burstiness within and between scenes. The transmission of a smooth stream can make efficient use of simple resource allocation models, such as constant-bit-rate or renegotiated constant-bit-rate services [19].

Reducing the peak transmission rate of the video stream is the primary goal of each of the smoothing algorithms. The algorithms, however, differ in what other performance metrics they consider. As a result, the various bandwidth smoothing algorithms generate transmission plans with different performance properties. The properties of the transmission schedules relate directly to the overhead of the transmission, transport, and playback of prerecorded constant-quality video. For example, this paper considers six smoothing algorithms that generate transmission schedules that

- minimize the number of changes in the transmission rate [18],
- minimize the variability of the bandwidth requirements [19],
- minimize the utilization of the client buffer [20],
- minimize the number of on-off segments in an on-off transmission model [25],
- change transmission rates only at periodic intervals [21],
- minimize general cost metrics through dynamic programming [22]

subject to limiting the peak transmission rate in the stream and avoiding underflow and overflow of the b-bit client buffer.

The appropriate optimization criterion depends on the underlying resource allocation model at the server and client sites, as well as the network. In a realistic setting, however, more than one criterion may have impact on the resource requirements, particularly when the components in the system have different performance goals. For example, low buffer utilization may appeal to the clients, whereas low bandwidth variability may appeal to service providers that wish to multiplex as many streams as possible. As a result, it becomes important to understand how well each smoothing algorithm performs across the range of possible optimization criteria. An algorithm that has near-optimal performance according to several metrics may be preferable to an algorithm is optimal for one metric and performs poorly for all the others. In this paper, we present a systematic comparison of bandwidth smoothing algorithms across a range of optimization criteria and video traces, with the goal of quantifying how well each algorithms performs according to each metric. Experimenting with a diverse set of video traces enables us to draw sound conclusions about both the performance of the various algorithms and the effectiveness of bandwidth smoothing in general.

The performance comparison draws on our library of twenty full-length, constant-quality video clips[1], digitized using a PC-based, motion-JPEG video capture testbed, as described in Section 2. By studying a range of different video streams (including a range of educational videos, action movies, and animated films), we can determine how much each type of video stream can benefit from each of the smoothing algorithms. For completeness, we also consider a number of publicly available MPEG traces [16]. Section 3 describes the six bandwidth smoothing algorithms, with an emphasis on the metrics they optimize as well as their computational complexity. Drawing on the video traces, Section 4 compares the smoothing algorithms and investigates the interaction between four key performance metrics

- peak bandwidth requirement
- variability of transmission rates
- number of rate changes
- client buffer utilization

that relate directly to the server, network, and client resources required for transmitting the smoothed video stream. In addition to evaluating the bandwidth smoothing algorithms, these experiments also highlight unique properties of the underlying video clips. These results motivate several possible directions for future research on the efficient transmission of prerecorded variable-bit-rate video, as discussed in Section 5.

[1]The video traces are available on the web at `http://www.cis.ohio-state.edu/~wuchi/Video/index.html`.

2 Compressed Video Sources

An effective comparison of bandwidth smoothing algorithms requires a large collection of video trace data to represent the diverse traffic in emerging multimedia services. However, most studies of video transmission techniques evaluate a small number of relatively-short compressed video clips, due to the scarcity of publicly-available traces. To facilitate a more comprehensive evaluation of the smoothing algorithms, we have generated a library of full-length, motion-JPEG encoded video traces [26, 27].

2.1 Video Capture Testbed

Quickly gathering large amounts of video trace data requires hardware support for video compression. The video capture testbed consists of a Pioneer Laser Disc player, a VHS player, a MiroVideo DC1tv capture board, and a Pentium-90 processor with 32 megabytes of memory. The MiroVideo Capture board is a motion-JPEG compression board containing the C-Cube Microsystems' motion-JPEG chip, the CL550. The motion-JPEG algorithm compresses each video frame using the JPEG still-picture standard [9]. The MiroVideo board digitizes the frames at 640×480 pixels and then subsamples them to 320×240 pixels with guaranteed VHS picture quality. By setting options on this board, the testbed can vary the quality factor used in compressing the video encoding. In particular, the overall picture quality can be changed by scaling the quantization levels for the frequency components produced by the DCT (discrete cosine transform) in the JPEG encoding algorithm. Each video sequence is encoded with a fixed quantization level, resulting in a constant-quality, variable-bit-rate stream.

Since motion-JPEG compresses each video frame independently, the traces do not capture the effects of inter-frame dependencies that would exist in MPEG-encoded streams [8, 16]. For a typical video source, an MPEG encoding would have smaller average frame sizes and larger short-term burstiness, due the mixture of interpolated (I), predictive (P), and bidirectional (B) frames. (The resultant M-JPEG streams used here are the same as an all I-frame encoded MPEG stream). A video server could limit the effects of this short-term variation through modest smoothing into a small client buffer. Consequently, the relative performance of bandwidth smoothing algorithms is more sensitive to the medium-term and long-term burstiness in the underlying video stream, particularly for a larger client buffer. Since a real-time MPEG encoder would not significantly affect the performance trends, except perhaps under small buffer sizes, the testbed employs the (order of magnitude) cheaper hardware that produces constant-quality, full-length, motion-JPEG video streams. For completeness, we also evaluate the bandwidth smoothing algorithms on publicly available MPEG-1 traces.

	Full Trace			Frame Sizes			
	Size (GB)	Time (min)	Rate (Mbps)	Avg (bytes)	Max (bytes)	Min (bytes)	CoV (bytes)
Beauty and the Beast	1.82	80	3.04	12661	30367	2701	0.283
Big	2.26	102	2.96	12346	23485	1503	0.192
Crocodile Dundee	1.82	94	2.59	10773	19439	1263	0.217
E.T. (quality 75)	1.24	110	1.51	6305	14269	1511	0.292
E.T. (quality 90)	1.78	110	2.17	9022	19961	2333	0.285
E.T. (quality 100)	3.11	110	3.78	15749	30553	6827	0.209
Home Alone 2	2.35	115	2.73	11383	22009	3583	0.218
Honey, I Blew Up the Kids	2.12	85	3.32	13836	23291	3789	0.230
Hot Shots 2	1.92	84	3.06	12766	29933	3379	0.254
Jurassic Park	2.50	122	2.73	11363	23883	1267	0.286
Junior	2.71	107	3.36	14013	25119	1197	0.228
NCAA Final Four (VHS)	1.21	41	3.95	16456	29565	2565	0.251
Rookie of the Year	2.22	99	2.98	12435	27877	3531	0.220
Seminar1 (VHS)	0.98	63	2.07	8604	10977	7181	0.069
Seminar2 (VHS)	1.08	68	2.12	8835	12309	1103	0.069
Seminar3 (VHS)	0.88	52	2.26	9426	11167	7152	0.073
Sister Act	2.06	96	2.86	11902	24907	1457	0.219
Sleepless in Seattle	1.72	101	2.28	9477	16617	3207	0.259
Speed	2.46	110	2.97	12374	29485	2741	0.219
Total Recall	2.34	109	2.88	11978	24769	2741	0.225

Table 1: **Video Movie Library Statistics**: This table shows the statistics for the clips in our video movie library. All sources are motion-JPEG encoded with a quality factor of 90, except for two versions of *E.T.* with quality factors of 75 and 100. In total, the traces represent 31 hours of video and 38.5 gigabytes of compressed data.

2.2 Video Library

Using this PC-based testbed, we have constructed a video library with twenty video clips, consisting of 31 hours of video and a total of 38.5 gigabytes of motion-JPEG compressed data. A separate script post-processes each video clip to generate a sequence of frame sizes, which drive the simulation experiments in Section 4. The video library includes clips with different lengths and subject matters, to represent the diversity of compressed video sources in emerging multimedia services. For example, the *Beauty and the Beast* video is an animated Walt Disney film that has scenes with a large number of high-frequency components as well as scenes with large areas of constant color. The rest of the movies are a mixture of conventional entertainment with a wide range of scene content, including digital effects and animations.

The library includes three versions of the film *E.T. - The Extra Terrestrial* with different quantization levels; the quality factors of 75, 90, and 100 correspond to 0.66, 0.94, and 1.64 bits-per-pixel, respectively, in the compressed video stream. With a coarser representation of the frequency com-



(a) *Seminar1* (b) *Jurassic Park* (c) *Sleepless in Seattle*

Figure 2: **Compressed Video Traces:** These plots show the frame sizes, averaged over three-second intervals, for a departmental seminar and two movies.

ponents, the video stream has smaller average and peak frame sizes, resulting in a lower bandwidth requirement for transmitting and receiving the movie; for example, a quality factors of 75, 90, and 100 result in average bit rates of 1.51, 2.17, and 3.78 megabits/second, respectively. The three versions of *E.T.* permit the performance evaluation in Section 4 to study the effectiveness of bandwidth smoothing techniques as a function of video quality. The remainder of the video traces in Table 1 have 0.94 bits-per-pixel, which corresponds to "excellent" picture quality [9].

To broaden the collection of traces, the library also includes a handful of sources from video cassette tapes. The *NCAA Final Four* video is a documentary describing the 1993 NCAA basketball tournament. This trace has a higher average bit rate than the other sources, by a fairly significant margin. In addition, the library includes three departmental seminars to study the impact of compression and bandwidth smoothing on educational video. These presentations were filmed with a single, stationary camera focusing on the screen for displaying the speaker's transparencies. This results in small bandwidth requirements and low variation in the frame sizes relative to the other videos, as shown in Figure 2. For the seminar video, the trace shows that a few smaller frames occur every minute or two, corresponding to brief intervals with an empty screen, when the speaker changes transparencies. In contrast to the seminar videos, the movies *Jurassic Park* and *Sleepless in Seattle* are more representative examples of the videos in our library. The compressed *Jurassic Park* stream in Figure 2(b) has larger frames, on average, in the first hour of the movie. The compressed *Sleepless in Seattle* stream exhibits larger bursts of large and small frames, as shown in Figure 2(c).

In addition to the M-JPEG traces that we have captured, we had obtained several publicly available MPEG-encoded video streams from Oliver Rose [2]. All the MPEG-1 streams (except *News_1*) are 40,000 frames in length. Thus, these streams are relatively shorter than the ones we have captured but nevertheless represent a rather diverse set of MPEG-encoded video streams. The statistics for

[2]Available via anonymous ftp from: ftp-info3.informatik.uni-wuerzburg.de

	Full Trace			Frame Sizes			
	Size (GB)	Time (min)	Rate (Mbps)	Avg (bytes)	Max (bytes)	Min (bytes)	CoV (bytes)
Asterix	0.10	22	0.67	2794	18423	39	0.901
ATP	0.10	22	0.66	2737	23858	36	0.932
Bond	0.11	22	0.73	3039	30575	240	1.057
Dino	0.06	22	0.39	1635	14955	111	1.127
Lambs	0.03	22	0.22	914	16779	37	1.530
MrBean	0.08	22	0.53	2206	28635	44	1.169
Mtv_1	0.11	22	0.74	3076	28651	47	0.937
Mtv_2	0.09	22	0.59	2473	31427	61	1.084
News_1	0.08	17	0.62	2584	24303	3	1.257
News_2	0.07	22	0.46	1920	23737	35	1.269
Race	0.14	22	0.92	3844	25303	525	0.688
Sbowl	0.11	22	0.71	2939	17606	37	0.796
Simpsons	0.09	22	0.56	2322	30048	43	1.112
Soccer_1	0.13	22	0.81	3392	23398	309	0.957
Soccer_2	0.12	22	0.75	3139	23788	370	0.846
Starwars	0.04	22	0.28	1165	15603	35	1.384
Talk_1	0.07	22	0.44	1818	13347	261	1.136
Talk_2	0.08	22	0.54	2240	16595	448	1.017
Terminator	0.05	22	0.33	1364	9946	40	0.931

Table 2: **MPEG Video Movie Library Statistics**: This table shows the statistics for the MPEG clips in our video movie library.

these clips are shown in Table 2.

3 Bandwidth Smoothing Algorithms

A multimedia server can substantially reduce the rate requirements for transmitting prerecorded video by transmitting frames into the client playback buffer in advance of each burst. A class of bandwidth smoothing algorithms capitalizes on *a priori* knowledge of the prerecorded stream to compute a server transmission schedule, based on the size of the playback buffer.

3.1 Overflow and Underflow Constraints

A compressed video stream consists of n frames, where frame i requires f_i bytes of storage. Without loss of generality, we assume that time is measured in units of frame slots. To permit continuous playback at the client site, the server must always transmit enough data to avoid buffer underflow, where

$$L(k) = \sum_{i=0}^{k} f_i$$

indicates the amount of data consumed at the client by frame k, where $k = 0, 1, \ldots, n-1$. Similarly, the client should not receive more data than

$$U(k) = L(k) + b$$

by frame k, to prevent overflow of the playback buffer (of size b)[3]. Consequently, any valid server transmission plan should stay within the area enclosed by these vertically equidistant functions, as shown in Figure 3(a). That is,

$$L(k) \leq \sum_{i=0}^{k} c_i \leq U(k)$$

where c_i is the transmission rate during frame slot i of the smoothed video stream.

A transmission schedule consists of a sequence of m linear segments, each with a constant bandwidth allocation r_j, $j = 1, 2, \ldots, m$, where time is measured in discrete frame slots. At time i the server transmits at rate $c_i = r_j$, where slot i occurs during run j. Together, the m bandwidth runs must form a monotonically-nondecreasing, piecewise-linear path that stays between the $L(k)$ and $U(k)$ curves. For example, Figure 3 shows a plan with $m=3$ runs, where the second run increases the transmission rate to avoid buffer underflow at the client playback buffer; similarly, the third run decreases

[3]This definition of the overflow constraint $U(k)$ assumes that the client removes frame k from the playback buffer into a separate decode buffer at time k. If the client has a single shared buffer, the underflow constraint is $U(k) = L(k-1)+b$.



Figure 3: **Computing Transmission Plans:** This figure shows the buffer underflow and overflow curves for a sample video stream. The resulting transmission plan consists of three constant-bit-rate runs that serve as a server schedule for transmitting video frames. A smoothing algorithm can optimize various performance metrics depending on how it selects the starting point and slope for each run.

the rate to prevent overflow. Bandwidth smoothing algorithms typically select the starting point for run $j+1$ based on the trajectory for run j. By extending the fixed-rate line for run j, the trajectory eventually encounters either the underflow or the overflow curve, or both, requiring a change in the server transmission rate.

3.2 Selecting Long Trajectories

Several different smoothing algorithms have been introduced that use both the $L(k)$ and $U(k)$ curves in computing the bandwidth runs in the transmission plans, based on the size of the client playback buffer. Given a starting point for run $j+1$, these algorithms select a trajectory that extends as far as possible to limit the number of bandwidth changes. As a result, the trajectory for each run must eventually reach both the overflow and the underflow curves, generating a *frontier* of possible starting points for the next run, as shown in Figure 3. The various bandwidth smoothing algorithms differ in how they select a starting point for run $j+1$ on rate increases and decreases, resulting in transmission plans with different performance properties:

- **MCBA:** To minimize the number of rate decreases, the *minimum changes bandwidth allocation* (MCBA) algorithm [18] performs a search operation on the frontier of each rate change for a starting point for the next run. This results in a transmission plan with the smallest possible number of rate changes (minimizes m), as well as the minimum peak bandwidth requirement. When implemented with a binary search, the MCBA algorithm has a worst-case complexity of $O(n^2 \log n)$, where the $\log n$ term arises from performing a binary search along the frontier of each run; on average, the algorithms run in $O(n \log n)$ time. An alternate implementation, based on an algorithm from the robotics literature, has $O(n)$ complexity [23]. A sample schedule in



(a) Min changes (MCBA) (b) Min variability (MVBA) (c) Min buffer (RCBS)

(d) Min on-off (ON-OFF) (e) Periodic changes (PCRTT) (f) Dynamic prog. (PCRTT-DP)

Figure 4: **Bandwidth Plans:** These graphs show the transmission plans generated by four different bandwidth smoothing algorithms, applied to the movie *Speed* and a 1 megabyte client playback buffer. For the PCRTT algorithm, the graph shows the plan with the largest possible interval size that would not overflow a 1 megabyte buffer.

shown in Figure 4(a).

- **MVBA:** Instead of minimizing the number of rate changes m, the *minimum variability bandwidth allocation* (MVBA) algorithm minimizes the variance in the rate requirements [19]. MVBA initiates bandwidth changes at the leftmost point along the frontier, for both rate increases and rate decreases. As a result, an MVBA transmission plan *gradually* alters the stream's rate requirement, sometimes at the expense of a larger number of small bandwidth changes. By avoiding a binary search along the frontier, the MVBA algorithm can have a worst-case complexity of $O(n^2)$. An alternate implementation of the algorithm can be derived that has $O(n)$ worst-case complexity [28]. A sample schedule in shown in Figure 4(b).

For a given client buffer size, the MCBA and MVBA bandwidth smoothing algorithms result in transmission plans that minimize the peak bandwidth and maximize the minimum bandwidth. Still, these algorithms differ in terms of rate variability, the frequency of rate changes, and client buffer utilization, as discussed in Section 4.

3.3 Smoothing at the Peak Rate

In addition to generating transmission plans, the MCBA and MVBA algorithms provide an efficient way to compute the minimum achievable peak transmission rate. The next two algorithms use this

Algorithm	Optimization	Complexity
MCBA [18, 23]	Minimum rate changes	$O(n)$
MVBA [19]	Minimum rate variability	$O(n)$
RCBS [20]	Minimum client buffer usage	$O(n)$
ON-OFF [25]	Minimum number of on/off periods	$O(n)$
PCRTT [21]	max spacing of rate changes	$O(n)$
PCRTT-DP [22]	General optimization model	$O(n^3)$

Table 3: **Bandwidth Smoothing Algorithms:** This table summarizes the key characteristics of each of the bandwidth smoothing algorithms.

rate to generate schedules with different performance properties:

- **RCBS:** Given a maximum bandwidth constraint r, the *rate-constrained bandwidth smoothing* (RCBS) algorithm generates a schedule with the smallest buffer utilization by transmitting frames as late as possible, subject to the rate constraint [20, 29]. Given the rate r, this algorithm minimizes the maximum buffer size required for the particular rate. This $O(n)$ algorithm starts with the last frame of the movie and sequences backwards toward the first frame. Any frame that exceeds the rate constraint is modified to the maximum rate constraint and then transmitted earlier. As shown in Figure 4(c), the RCBS plan follows the actual data rate for the movie rather closely, particularly for small buffer sizes.

- **ON-OFF:** Given a maximum bandwidth constraint r, the *on-off* algorithm generates a schedule that alternates between transmitting at the peak rate ("on" period) and not transmitting at all ("off" period), subject to the rate constraint [25]. The $O(n)$ on-off algorithm minimizes the number of on-off segments, subject to the rate constraint and the client buffer size, and results in transmission rates that fluctuate across time, as shown in Figure 4(d). Depending on the scheduling model at the server, and the availability of traffic shaping hardware, the on-off schedules may be easier to implement than the other transmission plans.

3.4 Periodic Time Intervals

Given the different starting points on the *frontiers*, the MCBA and MVBA algorithms select trajectories that extend as far as possible before reaching both the $L(k)$ and $U(k)$ curves. Other smoothing algorithms focus on the $L(k)$ curve in constructing a schedule; if necessary, these algorithms can iterate to compute a schedule that also satisfies the buffer constraint b for the $U(k)$ curve:

- **PCRTT:** In contrast to the four previous algorithms, the *piecewise constant rate transmission and transport* (PCRTT) algorithm [21] creates bandwidth allocation plans by dividing the video stream into fixed-size intervals. This $O(n)$ algorithm generates a single run for each interval by connecting the intersection points on the $L(k)$ curve, as shown in Figure 5; the slopes of these lines correspond to the rates r_j in the resulting transmission plan. To avoid buffer underflow, the PCRTT scheme vertically offsets this plan until all of the runs lie above the $L(k)$ curve. Raising

the plan corresponds to introducing an initial playback delay at the client site; the resulting transmission curve also determines the minimum acceptable buffer size to avoid overflow given the interval size, as shown in Figure 5. The algorithm results in periodic rate changes, as shown by the example in Figure 4(e).

- **PCRTT-DP:** Instead of requiring a rate change for each time interval, an extension to the PCRTT algorithm employs dynamic programming (DP) to calculate a minimum-cost transmission plan that consists of m runs [22]. Although dynamic programming offers a general framework for optimization, we focus on the buffer size b as the cost metric to facilitate comparison with the other smoothing algorithms. The algorithm iteratively computes the minimum-cost schedule with k runs by adding a single rate changes to the best schedule with $k-1$ rate changes. However, an exact solution, permitting rate changes in any time slot, would introduce significant computational complexity, particularly for full-length video traces. To reduce the computational overhead, a heuristic version of the algorithm [22] groups frames into intervals, as in Figure 5, when computing each candidate schedule; then, the full frame-level information is used to determine how far to raise the schedule to avoid buffer underflow. This algorithm has a computational complexity of $O(n^3)$.

As shown in Figure 4(f), the resulting PCRTT-DP algorithm, using a group size of 60 frames, produces bandwidth plans that are somewhat similar to MCBA plans, since both try to limit the number of rate changes. In contrast, the original PCRTT algorithm produces a schedule with a larger number of short runs, since the algorithm uses a single time interval throughout the video; in this example, a small interval size is necessary to avoid overflow of the client buffer. The RCBS plan changes the transmission rate in almost every time unit, except when large frames introduce smoothing at the peak rate. The next section compares the smoothing algorithms across a range of client buffer sizes, video clips, and performance metrics to evaluate these trade-offs in transmitting prerecorded, variable-bit-rate video. The properties of the various smoothing algorithms are summarized in Table 3.

4 Performance Evaluation

Using the traces from the video library, this section compares bandwidth smoothing algorithms based on a collection of performance metrics. These metrics include the peak rate requirements, the variability of the bandwidth allocations, the number of bandwidth changes, and the utilization of the playback buffer. By applying these metrics to server transmission plans, across a wide range of realistic client buffer sizes, the simulation experiments show cost-performance trends that affect the transmission, transport, and playback of compressed video. Since some of the algorithms implicitly introduce playback delay, we permit each algorithm to use the same playback delay to transmit data in advance for the first bandwidth run. For our experiments, we have allowed a maximum prefetch time (before playback begins) of 900 frames or 30 seconds. We note that depending on the movie, the size of the



Figure 5: **PCRTT Plan Creation:** This figure shows the creation of a PCRTT bandwidth allocation plan. First, the algorithm calculates the average frame size for each interval (dashed line). Then, the algorithm raises the plan to avoid buffer underflow. Based on the offset plan, the minimum buffer requirement is the maximum distance above the underflow curve.

buffer, and the smoothing algorithms that the prefetch delay was chosen to optimize the metrics for which they were created.

For the PCRTT and PCRTT-DP algorithms, which determine the buffer size as a byproduct of computing the bandwidth plan, we vary the window size (for PCRTT) and the number of rate changes (for PCRTT-DP) to generate a collection of plans, each with a corresponding buffer size. The fixed window size in the PCRTT algorithm can result in fluctuations in the performance metrics as the buffer size increases, since a smaller window size can sometimes result in a larger buffer requirement. The PCRTT-DP heuristic computes bandwidth plans based on groups of 60 for the M-JPEG streams (due to their substantially large number of frames) and 12 frames for the MPEG streams (to match the Group of Pictures pattern) to reduce the computation time; sample experiments with smaller group sizes resulted in similar values for the performance metrics. However, the frame grouping does limit the ability of the algorithm to compute bandwidth plans for small buffer sizes; for small buffer sizes, a more exact (and computationally expensive) version of the PCRTT-DP heuristic should produce statistics that resemble the MCBA results, since both algorithms compute transmission plans than limit the number of rate changes. The frame-grouping and rate-change parameters both limit the algorithm's ability to compute valid plans for small buffer sizes, since smoothing into a small buffer requires bandwidth changes on a very small time scale.

For a typical two-hour video ($n = 216,000$ frames), the MCBA, MVBA, RCBS, and PCRTT algorithms require a few seconds of computation time on a modern workstation. The RCBS algorithm generally executes in the smallest amount of time (after determining the rate constraint), followed

by the ON-OFF, PCRTT, MVBA, and MCBA algorithms (in that order); exact comparisons of computational overhead are difficult, since they would depend on the platform and the details of each implementation. The PCRTT-DP algorithm, using a group size of 60 frames for M-JPEG streams and allowing up to 3000 rate changes, requires about an hour to execute. Similarly, for the MPEG streams the PCRTT-DP algorithm uses group sizes of 12 and require about an hour to execute as well. Because the PCRTT-DP algorithm start with the number of rate changes $K = 1$ and iteratively calculates the minimal cost of each successive bandwidth change, calculating a plan that has 1000 bandwidth changes requires the calculation of all plans with fewer bandwidth changes. To speed this algorithm up, we calculated all the costs (in terms of the buffer size) for each sequence of frames (i, j), $0 < i < j \leq N$. This reduces the computational complexity of each bandwidth change to $O(n^2)$.

4.1 Peak Bandwidth Requirement

The peak rate of a smoothed video stream determines the worst-case bandwidth requirement across the path from the video storage on the server, the route through the network, and the playback buffer at the client site. Hence, most bandwidth smoothing algorithms attempt to minimize

$$\max_j \{r_j\}$$

to increase the likelihood that the server, network, and the client have sufficient resources to handle the stream. This is especially important if the service must reserve network bandwidth based on the peak rate, or if the client has a low-bandwidth connection to the network. In addition, reducing the maximum bandwidth requirement permits the server and the network to provide deterministic guarantees to a larger number of streams.

Figure 6 plots the peak rate $\max\{r_j\}$ as a function of the client buffer size for each of the motion-JPEG and MPEG clips. The graphs plot the minimum peak rate achieved by the MCBA, MVBA, RCBS, and ON-OFF algorithms. For each video, the peak rate decreases as the buffer size increases, with diminishing returns for larger buffer sizes. The same basic trends hold for each of the motion-JPEG and MPEG clips, as shown in Figure 6(a) and Figure 6(b), respectively, since motion-JPEG and MPEG encodings should have similar variability in frame sizes on the medium time scale. However, the MPEG clips typically show a more dramatic reduction in the peak rate for very small buffer sizes, since a small buffer allows the server to smooth over variations in frame sizes within an MPEG group-of-pictures. Also, the MPEG clips flatten sooner under large buffer sizes, due to the smaller average frame sizes and the shorter video lengths of the MPEG clips. This can be seen by comparing the peak rates for the motion-JPEG and MPEG clips under larger buffer sizes.



(a) Motion-JPEG clips (b) MPEG clips

Figure 6: **Minimum Peak Bandwidth Requirement:** These graphs plot the peak bandwidth as a function of the client buffer size for each of the motion-JPEG and MPEG video clips. The graphs plot the peak rate achieved by the MCBA, MVBA, RCBS, and ON-OFF algorithms, which minimize this metric.

The graphs in Figure 6 also show some variation between the different video clips. Under small buffer sizes, the movies with the largest variations in frame sizes also tend to have the largest peak bandwidth requirements, due to the limited ability to smooth large peaks. In Figure 6(a), the *Beauty and the Beast*, *E.T. (quality 100)*, and *NCAA Final Four* videos are the top three curves, while the *Seminar* videos have the lowest peak bandwidth requirements for buffer sizes less than 1 megabyte. For the three *E.T.* videos, the lower-quality encodings have lower peak rate requirements, due to the smaller frame sizes at each point in the video. In fact, under larger buffer sizes, the *E.T. (quality 75)* video actually has a *lower* peak bandwidth than the *Seminar* videos. For large client buffers, smoothing removes nearly all of the burstiness in the stream, yielding a plan that stays very close to the mean frame size of 6305 bytes; the three *Seminar* videos, digitized with a quality factor of 90, have larger average frame sizes (8604, 8835, and 9426 bytes). Thus, for small buffer sizes, the peak bandwidth requirement is generally driven by the *maximum* frame size, while for larger buffer sizes, the peak rate is driven mostly by the *average* frame size.

Although a large playback buffer can substantially reduce the peak rate, the addition of more buffer space offers diminishing returns beyond a certain point. Figure 7(a) further illustrates this effect by plotting the peak-bandwidth curves for *Beauty and the Beast*, *Crocodile Dundee*, and *Junior* with a linear scale on the x-axis. Each curve consists of a sequence of linear segments that become less steep as the buffer size increases, as shown in Figure 7(b) which plots the magnitude of the slopes. Typically, the peak bandwidth in a transmission plan is determined by a region of large frames in a small portion of the movie. Eventually, the buffer size grows large enough for this run to reach a region



(a) Peak bandwidth vs. b (b) Peak rate derivative

Figure 7: **Reducing the Peak Rate:** These plots highlight the relationship between the peak bandwidth metric and the client buffer size. In (a), we has selected 3 representative movies *Beauty and the Beast*, *Crocodile Dundee*, and *Junior*. In (b), the derivative (slope between peak bandwidth, buffer points) are shown, emphasizing the linear reduction in peak bandwidth requirement.

of small frames that can allow a more dramatic reduction in the bandwidth requirement; at this point, the peak rate may occur in a different part of video, also resulting in a new linear segment in the peak-bandwidth curve. Based on this observation, the server could characterize the buffer-bandwidth trade-off as a small number of linear curves, allowing efficient admission control policies that balance the use of network/server bandwidth and client buffer space. Recent theoretical work has formally proven that the peak-rate curve is piecewise-linear and convex [30].

While the MCBA, MVBA, RCBS, and ON-OFF algorithms minimize the peak bandwidth, PCRTT and PCRTT-DP transmission plans typically do not have substantially larger maximum bandwidth requirements. Figure 8 plots the peak bandwidth as a function of the client buffer size for two of the video clips. These results are representative of the performance of the PCRTT and PCRTT-DP algorithms on the other video clips. In general, the PCRTT algorithm is limited by its interval size, since it does not have full flexibility to smooth across intervals. Hence, the PCRTT algorithm has the most difficulty when a video clip has areas of sustained large frames followed by areas of small frames (or vice-versa). These regions require small interval sizes to avoid overflow and underflow of the client buffer. These small interval sizes, in turn, limit the algorithm's ability to smooth across larger time periods, resulting in a higher peak rate.

The PCRTT-DP plans often have smaller peak bandwidth requirements than the PCRTT algorithm, and are similar to the other algorithms. In fact, an exact version of PCRTT-DP algorithm, using a group size of 1 frame, would generate transmission plans that minimize the peak bandwidth. However, the grouping of frames can sometimes inflate the peak rate when a sequence of large frames



(a) *Final Four* (M-JPEG) *Mr. Bean* (MPEG)

Figure 8: **Peak Bandwidth Requirement Across All Algorithms:** These graphs plot the peak bandwidth as a function of the client buffer size for each of the bandwidth smoothing algorithms for two video clips.

fall within a single group, as shown in Figure 9. In this particular example, smoothing the peak over the previous group of 60 frames would result in a smaller peak bandwidth requirement at the expense of a larger buffer size. The MCBA, MVBA, RCBS, and ON-OFF algorithms are able to adjust the bandwidth requirement at any frame, allowing it to suitably adjust the start and end of the run at frame 149,000. Referring to Figure 9, note that this high-bandwidth run starts and ends less than one group of frames away from the corresponding run in the PCRTT-DP plan. Still, in most cases, the PCRTT-DP heuristic generates plans with nearly optimal peak bandwidth requirements.

4.2 Variability in Bandwidth Requirements

In addition to minimizing the peak bandwidth, a smoothing algorithm should reduce the overall *variability* in the rate requirements for the video stream [19]. Intuitively, plans with smaller rate variation should require fewer resources from the server and the network; more precisely, smoother plans have lower *effective bandwidth* requirements, allowing the server and the network to statistically multiplex the maximum number of streams [31]. Even under a deterministic model of resource reservation, the server's ability to change a stream's bandwidth reservation may depend on the *size* of the adjustment ($|r_{j+1} - r_j|$), particularly on rate *increases*. If the system does not support advance booking of resources, the server or the network may be unable to acquire enough bandwidth to start transmitting frames at the higher rate[4]. Since the video clips have different average rate requirements, Figure 10

[4]If the system cannot reserve resources for the higher bandwidth r_{j+1}, the video stream may have to adapt to a smaller rate to avoid terminating the remainder of the transfer. For example, with a *layered* encoding of the video stream, the server could reduce the transmission rate by sending only the higher priority components of the stream [32, 33]. To limit



Figure 9: **PCRTT-DP Frame Grouping:** This graph plots the PCRTT-DP and MCBA plans for the movie *Speed* with a 1-megabyte playback buffer. Using a group size of 60 frames, the PCRTT-DP plan has a larger peak-rate run because the region of large frames extends part way into adjoining groups. In contrast, the MCBA algorithm can reduce the peak rate by transmitting more of the large frames during a portion of the previous time interval without exhausting the playback buffer.

plots the *coefficient of variation*

$$\frac{\text{stdev}\{c_0, c_1, \ldots, c_{n-1}\}}{\frac{1}{n}\sum_{i=0}^{n-1} c_i}$$

to normalize the variability metric across the different streams, where the server transmits at rate c_i at time i.

For each of the video clips, the coefficient of variation decreases as a function of the buffer size. In general, the motion-JPEG and MPEG clips have similar performance trends, though the MPEG clips have higher variability under small buffer sizes, due to the differences in frame sizes within a group-of-pictures. In Figure 6(a), the *Beauty and the Beast*, *E.T. (quality 75)*, and *E.T. (quality 90)* videos exhibit the most bandwidth variability. Interestingly, the *E.T.* streams with *lower* quality factors have greater variability in the bandwidth requirements, as shown in Figure 11. Although a coarser encoding reduces the *average* frame size, some frame lengths decrease more than others, depending on the scale of detail in the scene; from the information in Table 1, the coefficient of variation for frame sizes is 0.29, 0.28, and 0.20 for quality factors of 75, 90, and 100, respectively. Under small buffer sizes, the larger variability in frame sizes translates into larger variability in the bandwidth requirements. For larger buffer sizes, the three versions of *E.T.* have similar bandwidth variability, due to the common long-term variation in scene content; the variability of the *E.T. (quality 75)* clip decreases more quickly, as a function of buffer size, since a larger playback buffer can absorb most of

the degradation in video quality at the client site, the server can raise the stream's rate as close to r_{j+1} as possible.



(a) Motion-JPEG clips (b) MPEG clips

Figure 10: **Minimum Bandwidth Variability:** These graphs plot the coefficient of variation (standard deviation normalized by the mean) of the bandwidth requirements as a function of the client buffer size for the MVBA algorithm, which minimizes this metric.

the variation in frame sizes for the lower quality stream.

While the MVBA plans consistently have the smallest variability in bandwidth requirements, the MCBA plans typically have similar performance, as shown in Figure 12. In fact, the coefficient of variation for the MCBA plans is rarely more than 5% higher than the corresponding MVBA plans, across the range of buffer sizes and collection of video clips in Figure 10. The videos that show a higher difference in bandwidth variability also show a higher difference in the number of bandwidth changes in the MCBA and MVBA plans. This suggests that the higher variability in the MCBA plans stems from its attempts to combine multiple bandwidth changes into a single transmission rate, rather than making gradual adjustments. Still, both algorithms achieve low variability across a wide range of video clips, while minimizing the peak rate and maximizing the minimum transmission rate.

In contrast, the RCBS plans have higher rate variability, particularly under larger buffer sizes, since the algorithm only transmits data early when it is necessary to avoid exceeding the peak rate later in the schedule. As a result, an RCBS plan often transmits small frames at a low rate, resulting in a much lower minimum bandwidth than the MVBA and MCBA algorithms. Hence, the increase in rate variability under the RCBS algorithm actually stems from the *small* transmission rates. The PCRTT and PCRTT-DP schedules have larger variability in bandwidth allocations. Because the PCRTT algorithm smooths bandwidth requests based on fixed interval lengths, it cannot smooth burst of large frames beyond the size of the interval, resulting in higher peaks and lower valleys. Under larger buffer sizes, the partitioning of the frames into fixed intervals plays a large role in determining the minimum amount of buffering required to have continuous playback of the video. Finally, the ON-OFF schedules



(a) Transmission plans (b) Coefficient of variation

Figure 11: **Rate Variability of *E.T.* Encodings:** These graphs evaluate the three traces of *E.T.* (with quality levels of 100, 90, and 75), using the MVBA algorithm and a 1 megabyte buffer. Despite reducing the bandwidth requirements, the coarser encodings exhibit greater rate variability, relative to the average frame size.



(a) *Jurassic Park* (M-JPEG) (b) *Soccer 2* (MPEG)

Figure 12: **Bandwidth Variability Across All Algorithms:** These graphs plot the coefficient of variation (standard deviation normalized by the mean) of the bandwidth requirements as a function of the client buffer for each of the bandwidth smoothing algorithms for two video clips.



(a) Motion-JPEG clips (b) MPEG clips

Figure 13: **Minimum Frequency of Bandwidth Changes:** These graphs plot the rate of bandwidth changes as a function of the client buffer size for the MCBA algorithm, which minimizes this metric.

have very high variability, since the transmission rates alternate between zero and the peak rate.

4.3 Number of Bandwidth Changes

In addition to reducing the variability in the resource requirements, bandwidth smoothing also decreases the frequency of rate changes. Decreasing the number of rate changes reduces the cost of negotiating with the network [15] to reserve link bandwidth for transporting the stream[5]. In addition, reducing the number of rate changes may also reduce complexity at the server, which must retrieve data from disk for each stream based on its scheduled rate. As a minor point, reducing the number of rate changes also decreases the size of the transmission schedule, though this is typically small in comparison to the size of the actual video frames. Figure 13 plots the minimum frequency of bandwidth changes, achieved by the MCBA algorithm. Since the video clips have different durations, the graphs plot the *frequency* of bandwidth changes

$$\frac{m}{n}$$

in changes per minute across a range of client buffer sizes.

For all of the smoothing algorithms and video traces, the client playback buffer is effective in reducing the frequency of rate change operations. In Figure 13(a), the bottom three curves correspond to the *Seminar* videos, which do not require many rate changes due to their small frame sizes and the

[5]To further reduce interaction with the network, each video stream could have a separate *reservation plan* for allocating network resources along the route to the client. This reservation plan could have fewer rate changes than the underlying transmission plan, at the expense of reserving excess link bandwidth [15, 19].



(a) *Jurassic Park* (M-JPEG) (b) *MTV 1* (MPEG)

Figure 14: **Bandwidth Change Frequency Across All Algorithms:** These graphs plot the rate of bandwidth changes as a function of the client buffer size for each of the bandwidth smoothing algorithms, except the RCBS algorithm. The rage change frequency for the RCBS plans remains above 800/minute for *Jurassic Park* and above 600/minute for *MTV 1*, even for very large buffer sizes.

low variability in their bandwidth requirements. The *NCAA Final Four* video requires the highest rate of bandwidth changes, due to the large frame sizes and long-term variations in scene content. For a 64 kilobyte buffer, this stream requires an average of 1.8 rate changes per minute under the MCBA plan. In contrast, the corresponding MVBA plan requires 8.5 rate changes per minute. In general, MCBA requires much fewer rate changes than the other algorithms, as shown in Figure 14. For some movies and buffer sizes, the MVBA plans have up to 14 times as many bandwidth changes as the corresponding MCBA plans. This occurs because the MVBA algorithm introduces a larger number of small rate changes to minimize the variability of bandwidth requirements in the server transmission plan.

As an extreme example, we compare the MCBA and MVBA algorithms on the 23-second video trace shown in Figure 15(a). For a 128 kilobyte buffer, the MVBA algorithm introduces 104 rate changes (55 increases and 49 decreases), while the MCBA plan has just three bandwidth changes, as shown in Figure 15(b). During the first 400 frames of the video segment, the frame sizes gradually increase over time. On this long stretch of increasing bandwidth requirements, the MVBA algorithm tends to follow the "curve" of the increase by generating a sequence of small rate increases. A similar effect occurs during the gradual decreases in frame sizes for the remainder video segment. In Figure 15(b), note that the area between the two plans, in the range of frames 12720 to 12900, is approximately equal to the size of the smoothing buffer. This suggests that the MVBA plan has filled the client buffer, requiring a more gradual response to the rate increases in the video segment. In



(a) Segment of *Jurassic Park* (b) MCBA and MVBA plans (c) PCRTT plan

Figure 15: **Gradual Changes in Frame Sizes:** This figure highlights the differences between the MCBA and MVBA plans for a 23-second segment of *Jurassic Park* under a 128-kilobyte playback buffer. The MVBA algorithm performs a large number of small bandwidth changes to track the gradual increases (decreases) in the frame sizes. In contrast, the MCBA plan initiates a smaller number of larger rate changes (3 changes vs. 104 in the MVBA plan). The corresponding PCRTT plan has 31 rate changes.

contrast, the MCBA plan has a nearly empty buffer, giving the algorithm greater latitude in adjusting the server transmission rate; referring to Figure 3, this is a case where the MCBA algorithm selects a starting point at the *rightmost* point along the frontier whereas the MVBA algorithm selects the *leftmost* point.

Although the MVBA plans often have fewer rate changes than the corresponding PCRTT plans, the PCRTT algorithm sometimes generates fewer rate changes under moderate buffer sizes. For these buffer sizes, the PCRTT algorithm is effective at combining several bandwidth runs of the MVBA algorithm into a single rate interval. For example, in Figure 15(c), the PCRTT algorithm generates only 31 rate changes, in contrast to the 104 changes in the corresponding MVBA plan. The PCRTT-DP algorithm produces bandwidth allocation plans that are very similar to the MCBA algorithm, since they both strive to minimize the number of rate changes; however, under smaller buffer sizes, the PCRTT-DP heuristic generate more bandwidth changes due to the frame-grouping factor. In contrast to the PCRTT algorithms, the RCBS plans tend to follow the sizes of the individual frames for most of the stream, except when some workahead transmission is necessary to avoid increasing the peak rate for transmitting the video. With a small client buffer, the RCBS algorithm requires nearly 1800 rate changes per minute, not much less than the maximum rate of 2400 changes per minute (for a 30 frames/second video). Although the number of rate changes decreases as the buffer size grows, the RCBS algorithm still generates significantly more bandwidth changes than the other algorithms except for extremely large buffer sizes.



(a) Motion-JPEG clips (b) MPEG clips

Figure 16: **Minimum Average Buffer Utilization:** These graphs plot the average buffer utilization as a function of the client playback buffer size for the RCBS algorithm, which minimizes this metric.

4.4 Buffer Utilization

Although bandwidth smoothing reduces the rate requirements for transmitting stored video, workahead transmission may consume significant buffer resources at the client site. For a given size b for the playback buffer, a smoothing algorithm could strive to limit buffer utilization while still minimizing the peak rate [20]. Reducing the buffer utilization allows the client to statistically share the playback space between multiple video streams, or even other applications. If the client application can perform VCR functions, such as rewinding or indexing to arbitrary points in the video stream, a bandwidth plan that limits buffer utilization also avoids wasting server and network resources on transmitting frames ahead of the playback point. With fewer future frames in the playback buffer, the client can cache multiple frames behind the current playback point, allowing the service to satisfy small VCR rewind requests directly at the client site. Although the client could statically allocate buffer space for rewind operation, this would reduce the effectiveness of bandwidth smoothing by offering a smaller value of b to the smoothing algorithm. Instead, we focus on the utilization of the playback buffer across time, to determine the average amount of rewind space available.

The utilization of the client buffer corresponds to how far the transmission schedule lies above the lower constraint curve $L(k)$. By design, RCBS plans stay as close to the $L(k)$ curve as possible, without violating the peak rate restriction. The RCBS plan has less than 15% buffer utilization for most of the video clips in Figure 16. In fact, an RCBS plan only reaches the $U(k)$ curve during the bandwidth runs that must transmit frames at the peak rate. For example, Figure 17(a) shows the buffer utilization across time for the RCBS algorithm for the motion-JPEG video *Crocodile Dundee* and an 11-megabyte client playback buffer. For comparison, the graph also includes the buffer utilization for a transmission



(a) RCBS and Inverse RCBS (b) MVBA (c) PCRTT

Figure 17: **Buffer Utilization:** This figure shows the buffer utilization over time for smoothing the movie *Crocodile Dundee* with an 11-megabyte playback buffer.

schedule that sends frames as *late* as possible, subject to the buffer and peak-rate constraints. This *inverse* RCBS algorithm maximizes client buffer utilization, and may be useful in supporting efficient fast-forward operations at the client and tolerating variation in network latency[6]. Any transmission schedule that minimizes the peak rate must have a buffer utilization that lies between these two curves. Note that the two curves meet at a common buffer utilization of 100% when both schedules must have a full client buffer to avoid exceeding the peak transmission rate.

Buffer utilization for RCBS plans is especially low for small values of b, where very few frames are transmitted in advance. For larger b values, even RCBS performs must perform more extensive smoothing to successfully minimize the peak rate. Still, the RCBS algorithm gives the client sites the greatest latitude in sharing the playback buffer amongst multiple streams or in supporting efficient rewind operations. The RCBS algorithm generates transmission plans with much lower buffer usage than the other algorithms, especially under small buffer sizes, as shown in Figure 18. The MCBA, MVBA, and ON-OFF plans have buffer utilizations of approximately 50% across most of the video traces, since these two algorithms do not differentiate between rate increases and rate decreases when computing bandwidth runs. Hence, the runs have a nearly even split between trajectories that hit $L(k)$ and trajectories that hit $U(k)$. Runs between the two constraint curves experience a progression in buffer utilization from 0% to 100%, or vice versa, as shown in Figure 17(b). The PCRTT plans typically have the highest buffer utilization. Drawing on the example in Figure 5, the PCRTT algorithm generates trajectories based on $L(k)$ and then raises the plan until no points remain below $L(k)$, as shown in Figure 5. As a result, the final plan has very few points that lie close to $L(k)$, as shown by the example in Figure 17(c).

[6]Bounded jitter can also be tolerated by incorporating the maximum delay variation into the smoothing constraints [19].



(a) *Speed* (M-JPEG) (b) *Asterix* (MPEG)

Figure 18: **Average Buffer Utilization Across All Algorithms:** These graphs plot the average buffer utilization as a function of the client playback buffer size for each of the bandwidth smoothing algorithms for two video clips.

5 Conclusions and Future Work

In this paper, we have compared a collection of bandwidth smoothing algorithms for compressed, prerecorded video. By capitalizing on the *a priori* knowledge of frame lengths, these algorithms can significantly reduce the burstiness of resource requirements for the transmission, transfer, and playback of prerecorded video. For small buffer sizes, the PCRTT algorithm is useful in creating plans that have near optimal peak bandwidth requirements. However, the PCRTT algorithm limits the ability of the server to smooth frames across interval boundaries. The MCBA and MVBA algorithms exhibit similar performance for the peak rate requirement and the variability of bandwidth allocations; the MCBA algorithm, however, is much more effective at reducing the total number of rate changes. The RCBS algorithm introduces a large number of rate changes, and a wide variability in the bandwidth requirements, to minimize the utilization of the client playback buffer. The ON-OFF algorithm also introduces a lot of variability, though the ON-OFF plans may be well-suited for systems that have hardware support for traffic shaping.

Future work can consider new smoothing algorithms that enforce a lower bound on the time between rate changes. The PCRTT algorithm serves as an initial approach to this problem, with some limitations in exploiting the playback buffer. In our experiments, we attempted to find the best interval size to use for the PCRTT algorithm given a fixed buffer size by calculating many interval lengths. Creating an efficient algorithm to find the best interval and interval offset, given a fixed buffer size, is a possible avenue for research. More generally, the use of dynamic programming in the PCRTT-DP algorithm offers a valuable framework for minimizing "costs" that are functions of

multiple performance metrics. Similarly, hybrids of the other smoothing algorithm should be effective in balancing the trade-offs between different metrics. For example, extensions to RCBS (or inverse RCBS) algorithm could operate over coarser time intervals to reduce the variability in the transmission plans without significantly changing the buffer utilization properties.

Ultimately, the construction of server transmission plans should depend on the actual configuration of the server and client sites, as well as the degree of network support for resource reservation and performance guarantees. For example, the server may have additional latitude in smoothing video streams if the client is willing to tolerate some loss in quality; for example, the server could avoid rate change operations by occasionally dropping frames, particularly if the stream has a layered encoding. These new schemes can broaden the family of bandwidth smoothing algorithms to tailor video transmission protocols to delay, throughput, and loss properties along the path from the server, through the communication network, to the client sites.

References

[1] D. Anderson, Y. Osawa, and R. Govindan, "A file system for continuous media," *ACM Transactions on Computer Systems*, pp. 311–337, November 1992.

[2] P.Lougher and D. Shepard, "The design of a storage server for continuous media," *The Computer Journal*, vol. 36, pp. 32–42, February 1993.

[3] D. Kandlur, M. Chen, and Z. Shae, "Design of a multimedia storage server," in *Proceedings of the IS&T/SPIE Symposium on Electronic Imaging Science and Technology*, February 1994.

[4] D. Gemmell, J. Vin, D. Kandlur, P. Rangan, and L. Rowe, "Multimedia storage servers: A tutorial," *IEEE Computer Magazine*, vol. 28, pp. 40–49, May 1995.

[5] C. Federighi and L. Rowe, "A distributed hierarchical storage manager for a video-on-demand system," in *Proceedings of the IS&T/SPIE Symposium on Electronic Imaging Science and Technology*, February 1994.

[6] C. Aras, J. Kurose, D. Reeves, and H. Schulzrinne, "Real-time communication in packet switched networks," *Proceedings of the IEEE*, vol. 82, pp. 122–139, January 1994.

[7] H. Zhang, "Service disciplines for guaranteed performance service in packet-switching networks," *Proceedings of the IEEE*, vol. 83, pp. 1374–1396, October 1995.

[8] D. L. Gall, "MPEG: A video compression standard for multimedia applications," *Communications of the ACM*, vol. 34, pp. 46–58, April 1991.

[9] G. K. Wallace, "The JPEG still picture transmission standard," *Communications of the ACM*, vol. 34, pp. 30–44, April 1991.

[10] I. Dalgic and F. A. Tobagi, "Performance evaluation of ATM networks carrying constant and variable bit-rate video traffic," *IEEE Journal on Selected Areas in Communications*, vol. 15, August 1997.

[11] T. V. Lakshman, A. Ortega, and A. R. Reibman, "Variable bit-rate (VBR) video: Tradeoffs and potentials," *Proceedings of the IEEE*, vol. 86, May 1998.

[12] E. P. Rathgeb, "Policing of realistic VBR video traffic in an ATM network," *International Journal of Digital and Analog Communication Systems*, vol. 6, pp. 213–226, October–December 1993.

[13] S. S. Lam, S. Chow, and D. K. Yau, "An algorithm for lossless smoothing of MPEG video," in *Proc. ACM SIGCOMM*, pp. 281–293, August/September 1994.

[14] A. R. Reibman and A. W. Berger, "Traffic descriptors for VBR video teleconferencing over ATM networks," *IEEE/ACM Transactions on Networking*, vol. 3, pp. 329–339, June 1995.

[15] M. Grossglauser, S. Keshav, and D. Tse, "RCBR: A simple and efficient service for multiple time-scale traffic," *IEEE/ACM Transactions on Networking*, December 1997.

[16] O. Rose, "Statistical properties of MPEG video traffic and their impact on traffic modeling in ATM systems," in *Proceedings of Conference on Local Computer Networks*, pp. 397–406, October 1995.

[17] W. Feng and S. Sechrest, "Critical bandwidth allocation for delivery of compressed video," *Computer Communications*, vol. 18, pp. 709–717, October 1995.

[18] W. Feng, F. Jahanian, and S. Sechrest, "Optimal buffering for the delivery of compressed prerecorded video," *ACM Multimedia Systems Journal*, September 1997.

[19] J. D. Salehi, Z.-L. Zhang, J. F. Kurose, and D. Towsley, "Supporting stored video: Reducing rate variability and end-to-end resource requirements through optimal smoothing," *IEEE/ACM Transactions on Networking*, vol. 6, pp. 397–410, August 1998.

[20] W. Feng, "Rate-constrained bandwidth smoothing for the delivery of stored video," in *Proceedings of IS&T/SPIE Multimedia Networking and Computing*, pp. 58–66, February 1997.

[21] J. M. McManus and K. W. Ross, "Video on demand over ATM: Constant-rate transmission and transport," *IEEE Journal on Selected Areas in Communications*, pp. 1087–1098, August 1996.

[22] J. M. McManus and K. W. Ross, "A dynamic programming methodology for managing prerecorded VBR sources in packet-switched networks," *Telecommunications Systems*, vol. 9, 1998.

[23] J. Zhang and J. Hui, "Applying traffic smoothing techniques for quality of service control in VBR video transmissions," *Computer Communications*, vol. 21, pp. 375–389, April 1998.

[24] Z. Jiang and L. Kleinrock, "General optimal video smoothing algorithm," in *Proc. IEEE INFOCOM*, pp. 676–684, April 1998.

[25] J. Zhang and J. Hui, "Traffic characteristics and smoothness criteria in VBR video transmission," in *Proc. IEEE International Conference on Multimedia Computing and Systems*, June 1997.

[26] W. Feng, *Video-On-Demand Services: Efficient Transportation and Decompression of Variable-Bit-Rate Video*. PhD thesis, University of Michigan, April 1996.

[27] W. Feng and J. Rexford, "A comparison of bandwidth smoothing techniques for the transmission of prerecorded compressed video," in *Proc. IEEE INFOCOM*, April 1997.

[28] J. Salehi, *Scheduling Network Processing on Multimedia and Multiprocessor Servers*. PhD thesis, University of Massachusetts – Amherst, September 1996.

[29] J. K. Dey, S. Sen, J. Kurose, D. Towsley, and J. Salehi, "Playback restart in interactive streaming video applications," in *Proc. IEEE Conference on Multimedia Computing and Systems*, pp. 458–465, June 1997.

[30] J. Rexford and D. Towsley, "Smoothing variable-bit-rate video in an internetwork," in *Proc. SPIE Conference on Performance and Control of Network Systems*, pp. 345–357, November 1997.

[31] Z.-L. Zhang, J. F. Kurose, J. D. Salehi, and D. Towsley, "Smoothing, statistical multiplexing, and call admission control for stored video," *IEEE Journal on Selected Areas in Communications*, August 1997.

[32] L. Rowe, K. Patel, B. Smith, and K. Liu, "MPEG video in software: Representation, transmission, and playback," in *Proc. High Speed Networking and Multimedia Computing Symposium*, February 1994.

[33] P. Pancha and M. E. Zarki, "Prioritized transmission of variable bit rate MPEG video," in *Proc. IEEE GLOBECOM*, pp. 1135–1139, 1992.