


Using GLU/GLUT Objects

- GLU/GLUT provides very simple object primitiv



GLU/GLUT Objects

- Each glu/glut object has its default size, position, and orientation
- You need to perform modeling transformation to make it right for you




`glutWireCube(1.0)` - 'wire' means wire frame

Put a 1x1x1 cube with its center at world (0,0,0)

To create a 2 x 0.1 x 2 table top - need to call `glScalef(2, 0.1, 2)` before you call `glutWireCube(1.0)`

`gluCylinder()`

- Three steps to create a cylinder




- Create a GLU quadric object
`GLUQuadricObj *p = gluNewQuadric();`
- Set to wire frame mode
`gluQuadricDrawStyle(GLU__LINE);`
- Derive a cylinder object from p
`gluCylinder(p, base, top, height, slice, stacks)`

base radius top radius height
num. of vertical lines
num. of horizontal lines

The default position is also with base at $z = 0$ plane

`glutWireCone()`

- Use `glutWireCone` and `gluCylinder` to make a lamp



`glutWireCone(base, height, slices, stacks)`

- A polygon approximation of a cone.

Default position: its base at $Z = 0$ plane

base: the width of its base

height: the height of the cone

slices: the number of vertical lines used


to make up the cone

stake: the number of horizontal lines used

to make up the cone

glutWireTeapot()

- The famous Utah Teapot has become an unofficial computer graphics mascot




glutWireTeapot(0.5) -

Create a teapot with size 0.5, and position its center at (0,0,0)

Again, you need to apply transformations to position it at the right spot

Transformations


- Two ways to specify transformations
 - (1) Each part of the object is transformed independently relative to the origin
- Not the OpenGL Way!**



Relative Transformation


A better (and easier) way:

- (2) Relative transformation: Specify the transformation for each object relative to its parent




Object Dependency

- A graphical scene often consists of many small objects
- The attributes of an object (positions, orientations) can depend on others




Hierarchical Representation - Scene Graph

- We can describe the object dependency using a tree structure



Relative Transformation

Relative transformation: Specify the transformation for each object relative to its parent




Relative Transformation (2)

Step 2: Rotate the lower arm and all its descendants relative to its local y axis by -90 degree





Relative Transformation (3)

- Represent relative transformations using scene graph



Do it in OpenGL

- Translate base and all its descendants by (5,0,0)
- Rotate the lower arm and its descendants by -90 degree about the local y



```

glMatrixMode(GL_MODELVIEW);
glLoadIdentity();

... // setup your camera

glTranslatef(5,0,0);



Draw_base();

glRotatef(-90, 0, 1, 0);

Draw_lower_arm();
Draw_upper_arm();
Draw_hammer();
  
```



A more complicated example

- How about this model?




Do this ...

- Base and everything – translate (5,0,0)
- Left hammer – rotate 75 degree about the local y
- Right hammer – rotate -75 degree about the local y



Depth-first traversal

- Program this transformation by depth-first traversal




```

Do ____ transformation(s)
Draw base
Do ____ transformation(s)
Draw left arm
Do ____ transformation(s)
Draw right arm
  
```

What are they?

How about this?



Translate(5,0,0)

Draw base

Rotate(75, 0, 1, 0)

Draw left hammer

~~Rotate(-75, 0, 1, 0)~~

Draw right hammer

What's wrong?!

Something is wrong ...

- What's wrong? – We want to transform the right hammer relative to the base, not to the left hammer

How about this?

Do Translate(5,0,0)

Draw base

Do Rotate(75, 0, 1, 0)

Draw left hammer

~~Do Rotate(-75, 0, 1, 0)~~

Draw right hammer

We should **undo the left hammer transformation** before we transform the right hammer

Need to undo this first

What's wrong?!

Undo the previous transformation(s)

- Need to save the modelview matrix right after we draw base

Initial modelView M

Translate(5,0,0) -> M = M x T

Draw base

Rotate(75, 0, 1, 0)

Draw left hammer

Rotate(-75, 0, 1, 0)

Draw right hammer

Undo the previous transformation means we want to restore the Modelview Matrix M to what it was here

i.e., save M right here

...
And then restore the saved Modelview Matrix

OpenGL Matrix Stack

- We can use OpenGL Matrix Stack to perform matrix save and restore

Initial modelView M

Do Translate(5,0,0) -> M = M x T

Draw base

Do Rotate(75, 0, 1, 0)

Draw left hammer

Do Rotate(-75, 0, 1, 0)

Draw right hammer


* Store the current modelview matrix
- Make a copy of the current matrix and **push** into OpenGL Matrix Stack call `glPushMatrix()`

- continue to modify the current matrix

* Restore the saved Matrix
- **Pop** the top of the Matrix and copy it back to the current Modelview Matrix:
Call `glPopMatrix()`

Push and Pop Matrix Stack

- A simple OpenGL routine:



```

glTranslate(5,0,0)
Draw_base();
glPushMatrix();

glRotate(75, 0,1,0);
Draw_left_hammer();

glPopMatrix();
glRotate(-75, 0,1,0);
Draw_right_hammer();
    
```

Push and Pop Matrix Stack

- Nested push and pop operations

